

## SuperVoid Systems, LLC

1172 County Road 24  
Prattville, AL 36067-8243  
[www.supervoid.com](http://www.supervoid.com)  
Texas Registered Engineering Firm F-17554

Larry W. Primm  
334-730-3614  
David S. Primm, P.E.  
334-221-5761

September 13, 2023

### Project Submittal:

Re: **SuperVoid - Smart Void® Utility Protection Systems**  
**UPS-12 Series Utility Protection System with Clamp Hangers**

**Project:** Samsung SAS T-PJT  
Taylor, TX

**Submitted to:** Michael Hutchcraft  
Kilgore  
Round Rock, Texas

**Architect:** Page Southerland Page, Inc.  
Austin, Texas

**Consulting Engineer:** Derek C. Gaskamp, P.E.  
Infinity MEP Consultants  
Austin, Texas

**Submitted By:** David W. S. Primm, P.E.  
Chief Engineer

### SuperVoid Systems, LLC

Prattville, Alabama  
Cell: 334-221-5761

[primmd@supervoid.com](mailto:primmd@supervoid.com)  
[www.supervoid.com](http://www.supervoid.com)

Alabama PE No. 33265

Alabama Certificate of Authorization No. CA-5306-E


Colorado PE No. 52091

Mississippi PE No. 27016

Mississippi Certificate of Authorization No. 28319

Texas PE No. 121465

Texas Registered Engineering Firm F-17554



**Please be advised that we have reviewed the project documents. The geotechnical engineer states that the Potential Vertical Rise (PVR) for the soil at this site are calculated to be up to 4.5 inches. We recommend the UPS-12 Series, 12 inch deep SuperVoid Smart Void® Utility Protection System with SuperVoid Clamp Hanger Hardware for under slab piping in all areas on this project. This system has historically offered satisfactory utility protection for PVRs up to about 7-8 inches. The UPS-12 Series system should offer the protection required for the plumbing system, is cost effective, and is relatively easy to install correctly. Please direct question or comments about this recommendation to David S. Primm, P.E., SuperVoid Chief Engineer.**

# SUPERVOID - UTILITY PROTECTION SYSTEM UPS-12

SuperVoid basis of design assumes that the void space will be drained, and that the hanger rods will remain in a straight, plumb, undamaged condition prior to concrete slab placement. Carton forms should be pre-punctured to accommodate the hanger rods. Hanger rods shall not be used to puncture carton forms as this may damage the rods.

Nominal 24" Granular Non-Cohesive Backfill Covering Over the TOP of the UPS Unit *Backfill NOT SHOWN FOR CLARITY*



**WHERE 24" OF BACKFILL COVER OVER THE TOP OF THE UPS UNIT IS NOT ACHIEVABLE, A 1" DIAMETER SCHEDULE 40 PVC SLEEVE SHOULD EXTEND FROM THE BOTTOM OF THE PLATE WASHER TO THE TOP OF THE SUPERVOID CLAMP HANGER.**

**COARSE CONCRETE SAND BACKFILL IS RECOMMENDED**

DO NOT COMPACT TO HIGH DENSITY

DO NOT RUN OVER WITH EQUIPMENT WITHOUT FIRST TAKING MEASURES TO PREVENT DAMAGE TO THE UTILITY PROTECTION SYSTEM.

<b>UPS-1214 System</b>
- 12"d x 14"w (for ≤ 6" Pipe dia.)
<b>UPS-1216 System</b>
- 12"d x 16"w (for ≤ 10" Pipe dia.)
<b>UPS-1218 System</b>
- 12"d x 18"w (for ≤ 12" Pipe dia.)



# SUPERVOID - UTILITY PROTECTION SYSTEM UPS-12

SuperVoid basis of design assumes that the void space will be drained, and that the hanger rods will remain in a straight, plumb, undamaged condition prior to concrete slab placement. Carton forms should be pre-punctured to accommodate the hanger rods. Hanger rods shall not be used to puncture carton forms as this may damage the rods.

Nominal 24" Granular Non-Cohesive Backfill Covering Over the TOP of the UPS Unit *Backfill NOT SHOWN FOR CLARITY*

**WHERE 24" OF BACKFILL COVER OVER THE TOP OF THE UPS UNIT IS NOT ACHIEVABLE, A 1" DIAMETER SCHEDULE 40 PVC SLEEVE SHOULD EXTEND FROM THE BOTTOM OF THE PLATE WASHER TO THE TOP OF THE SUPERVOID CLAMP HANGER.**



**COARSE CONCRETE SAND BACKFILL IS RECOMMENDED**

DO NOT COMPACT TO HIGH DENSITY

DO NOT RUN OVER WITH EQUIPMENT WITHOUT FIRST TAKING MEASURES TO PREVENT DAMAGE TO THE UTILITY PROTECTION SYSTEM.

<u>UPS-1214 System</u>
- 12"d x 14"w (for ≤ 6" Pipe dia.)
<u>UPS-1216 System</u>
- 12"d x 16"w (for ≤ 10" Pipe dia.)
<u>UPS-1218 System</u>
- 12"d x 18"w (for ≤ 12" Pipe dia.)


PVC SLEEVE FOR SHALLOW PLACEMENT



# SUPERVOID - SMART VOID® UPS - 12 SERIES

## 12 DEEP" UTILITY PROTECTION SYSTEM

### PIPE VOID ... SIMPLIFIED



Nominal 24" Granular Non-Cohesive Backfill  
 Covering TOP of Pipe Void Unit  
 Backfill to top of trench with Non-Cohesive material  
DO NOT COMPACT TO HIGH DENSITY  
DO NOT RUN OVER WITH EQUIPMENT

6" Sand Bedding, Typ

SV - Rib Retainers  
 15" Tall for Typ. Installation  
 24" Tall required for shallow pipe applications

SuperVoid  
 UPS-1214 Unit with  $\frac{7}{16}$ "  
 Thick OSB Substrate

2" x 2" x  $\frac{3}{16}$ " Min. Steel Plate

All Pipe Hanger & Rod Hardware Shall Be 304 or 18-8 Stainless Steel

SuperVoid Clamp Hanger Spaced every 4 feet and at junctions. Hanger Rod shall remain in vertical orientation during backfill, placement of carton forms, and placement of concrete slab.

There is typically 6 in. of sand bedding between the top of the void and the bottom of the pipe, but the pipe placement within the backfill envelope may be variable to allow for non-typical installation and vertical constraints, Note: Taller Rib Retainers may be required.

3.5 oz Non-Woven Geo-Textile Wrapped Over Void Units and Down the Sides, Like a Tablecloth

TYPICAL, NOT TO SCALE

<b>UPS-1214 System</b>
- 12"d x 14"w (for ≤ 6" Pipe dia.)
<b>UPS-1216 System</b>
- 12"d x 16"w (for ≤ 10" Pipe dia.)
<b>UPS-1218 System</b>
- 12"d x 18"w (for ≤ 12" Pipe dia.)
<b>UPS-1224 System</b>
- 12"d x 24"w (for ≤ 18" Pipe dia.)

**NOTE** Where pipes exit the building, at least the last two hanger rods should be sheathed with the **PVC sleeve** as shown on isometric drawing sheet.

# SUPERVOID - CLAMP HANGER - TYPICAL

All materials shall be  
Stainless Steel, 304 or 18-8

Coupling  
Nut Welded  
in place


Bar Stock

Clamp Bolt

Pipe Size	Rod Thread	Hanger Thickness	Hanger Width	Coupling Nut	Clamping Bolts
2"	1/2" - 13	1/8"	1-1/4"	1/2" - 13 x 1-1/4"	3/8"
3"	1/2" - 13	1/8"	1-1/4"	1/2" - 13 x 1-1/4"	3/8"
4"	1/2" - 13	1/8"	1-1/4"	1/2" - 13 x 1-1/4"	3/8"
6"	5/8" - 11	1/8"	1-1/2"	5/8" - 11 x 1-3/4"	3/8"
8"	3/4" - 10	3/16"	1-3/4"	3/4" - 10 x 2-1/4"	1/2"
10"	7/8" - 9	1/4"	1-3/4"	7/8" - 9 x 2-1/2"	1/2"
12"	7/8" - 9	1/4"	2"	7/8" - 9 x 2-1/2"	3/4"
14"	1" - 8	1/4"	2-1/2"	1" - 8 x 2-1/2"	3/4"

FIRE WATER SERVICE ENTRY STABILIZER, FOR 8IN PIPE  
BY SUPERVOID SYSTEMS, LLC  
ALL COPYRIGHT & PATENT RIGHTS RESERVED  
DRAWING DATE: MAY 25, 2023

SUPERVOID SYSTEMS, LLC  
DAVID PRIMM, P.E.: 334-221-5761  
PRIMMD@SUPERVOID.COM  
LARRY PRIMM: 334-730-3614  
LPRIMM@SUPERVOID.COM



THE FIRE WATER SERVICE ENTRY STABILIZER AS PROVIDED BY SUPERVOID SYSTEMS, LLC IS CONSTRUCTED FROM TYPE 304 STAINLESS STEEL WITH 18-8 STAINLESS STEEL FASTENERS. ALL HEX CAP SCREWS ARE MINIMUM  $\frac{1}{2}$ " IN DIAMETER. ALL ANCHORS ARE  $\frac{1}{2}$ "X7" WEDGE ANCHORS. IN THIS CONFIGURATION THE RATED CAPACITIES ARE BELOW:

MINIMUM ULTIMATE THRUST RESISTANCE RATING: 38 KIPS

MINIMUM ULTIMATE UPLIFT RESISTANCE RATING: 33 KIPS

ESTIMATED MAXIMUM THRUST FORCE FOR 8" PIPE AT 200PSI: 10 KIPS

UPLIFT FORCES SHOULD BE NEGLIGIBLE AS THE SUPERVOID UTILITY PROTECTION SYSTEM WILL BE POSITIONED UNDER THE PIPE AT THE FACE OF THE PERIMETER BEAM AND UNDER THE BUILDING FOUNDATION.



Project	
Piping	2017
Anywhere	

### Installation Instructions

The Geo-Fabric prevents subsequent lateral infiltration of soil into the void space. Be sure to seal the Void.


Cover Void Form and Substrate completely including top and sides with 3.5 - 4 oz. Non-Woven Geo-Fabric, all fabric longitudinal end laps should be 8-10".

Place the fabric on the adjacent ground extending 4-6" laterally at the base of the Void Form, or if the underlying soil is soft, set the void form on top of the Geo-Fabric, pull over the top of the void form, lap fabric a minimum of 6-8" and secure.

Insure that the Geo-Fabric is continuous. Inspect, Tuck, Straighten, Stabilize, Refit, Geo-Fabric prior to backfill. Repair or replace any damaged Geo-Fabric material.

Commonly available, standard duty 7/16" OSB as approved Substrate Cover Sheet.

### Under-Slab Pipe/Conduit Voids Plumbing & Conduits Void Forms - Earth Retaining Geo - Fabric Instructions



### Back Filling Pipe Void

Use Non-Cohesive Fill Materials for top and side cover materials. (Medium to Course Sand)

**\*\*Note...** The backfill material on top of the Pipe Void System serves as a weighted ballast. When the underlying "Expansive Soil" generates uplift pressures, the mass or weight of the backfill cover (Sand) resists the uplift and the void system absorbs and interrupts the soil pressure and vertical/lateral movement. **\*\***

Cover Top of Voids a minimum of 24 - 30", when possible. The elevation of the piping may be installed at any elevation above the top of the OSB substrate and 4" - 6" of recommended minimum sand cover.

When deep installations require stepping back slopes for excavation safety reasons, the initial non-cohesive fill material may be discontinued above 30" - 36" of height above the top of the void form. Native or other suitable types of materials may be used to complete the filling process with zero to minimal compaction recommended. High density compaction of fill materials is not recommended or required.

**Do Not Drive Equipment Over An Installed System!!**

Always practice and follow fully all applicable safety regulations. Call SuperVoid (334) 730-3614 (Larry) or (334) 251-5761 (David) for any questions or further direction.

SuperVoid - Smart Void® Pipe Void - "Simplified"

SUPERVOID

\* 1172 County Road 24 \* Prattville, AL 36067-8243 \* 334.730.3614  
© All Copyright & Patent Rights Reserved - SuperVoid - 2017

04-2017

Revised:

Revised:

Drawn By: LWP

SHEET

SV-01

Division \_\_\_\_\_

Sections \_\_\_\_\_

## **GENERAL SPECIFICATIONS FOR UTILITY PROTECTION SYSTEMS**

### 1. Overview:

This specification covers Sacrificial Utility Protection Pipe Void Form Systems, hereinafter referred to as "Utility Protection Systems". Utility Protection Systems shall always be used in conjunction with Rigid Retainers as a **SYSTEM** to maintain void spaces below critical building systems during and after construction. Rigid Retainers are covered by a separate specification. Utility Protection Systems serve as sacrificial falsework, which isolate critical building systems, such as utility pipes and electrical conduits, from the potentially damaging effects of expansive soils. The Utility Protection Systems furnished for this project shall be in accordance with these specifications and in reasonably close conformity with the lines, grades, design and dimensions shown on the plans or as established by the Engineer. The Utility Protection Systems shall be resistant to water and UV rays and shall be chiefly comprised of carbon steel expanded metal, which is structurally efficient and biodegradable. The carbon steel shall contain a minimum of 40% RECYCLED material. In situations where two or more specifications apply to this work, the most stringent requirements shall govern.

### 2. Utility Protection Systems Structure:

- A. Utility Protection Systems shall provide a dimensionally stable void space, maintaining uniform separation between the base soil and the critical building systems. The Utility Protection Systems shall have sufficient structural strength to maintain the intended void space while experiencing the anticipated construction loads.
- B. The Utility Protection Systems shall be designed to perform as sacrificial falsework and shall remain in place after construction and shall not be reused.
- C. Serving as a structural fuse, Utility Protection Systems shall reduce the accumulation of forces on critical building systems which can result from soil movement. The Utility Protection Systems shall absorb or redirect the forces of soil movements by: crumpling, crushing, collapsing, deforming, material section degradation, soil extrusion, open corrugation load span designs or combination of any or all load relief design functions.

### 3. Utility Protection Systems Material:

- A. Utility Protection Systems shall be constructed from Carbon Steel Expanded Metal, Types I & II, conforming to ASTM F1267 and shall be assembled when required with 15ga. galvanized steel C-Rings.
- B. The carbon steel shall conform to ASTM A1011 and contain a minimum of 40% RECYCLED material.
- C. All assembly and/or fabrications of the Utility Protection Systems shall occur entirely within the United States.
- D. The Utility Protection Systems material shall not promote the formation or emergence of mold spore, organic or other biological colonization.



E. The Utility Protection Systems must be able to be delivered and stored unprotected in the open jobsite environment for a minimum of 90 days without loss of design strength.

4. Utility Protection Systems Material, Minimum Physical Properties Requirements:

- A. Utility Protection Systems shall be naturally waterproof in terms of its intended use in this section.
- B. Utility Protection Systems shall have negligible buoyancy.
- C. Utility Protection Systems shall maintain structural integrity in 100% relative humidity.
- D. Utility Protection Systems material shall not emit offensive off-gassing odors during decomposition.
- E. The structural integrity of the Utility Protection Systems shall be unaffected by high/low ambient temperatures and elevated surface temperatures from direct sunlight extremes, above or sub-freezing, frozen soil and ice buildup.
- F. Utility Protection Systems must have an industry history of providing consistent performance integrity during and after all types of weather event applications, while in readiness storage or installed, without the threat of partial or full section premature collapse during concrete casting.
- G. Utility Protection Systems strength shall not be affected by becoming damp, wet, or when completely submerged in standing water.
- H. Utility Protection Systems must be fire-resistant

5. Utility Protection Systems Material, Minimum Performance Requirements:

- A. The Utility Protection Systems (system) shall be designed to provide sufficient dynamic live and dead load support capacities of but not limited to all loads common to this type of construction;
  - Installation of utility piping and/or conduit – dead/live loads
  - Placement of backfill materials (See Bedding and Backfill material sub-section 6)
  - Manpower and foot traffic loads
- B. Sub-standard Utility Protection Systems cover sheet substrates, can affect desired performance; use only the types of substrates as those approved for use and recommended by the Utility Protection Systems manufacturer.
- C. Substrate materials shall originate from FSC (Forest Stewardship Council, United States) mills and be in new or like new condition, performing to APA (The Engineered Wood Association) current standards.

6. Bedding and Backfill Material:

- A. Select Bedding and Backfill material shall be placed on both sides of the Utility Protection System shall embed the system up to at least the top of the pipe.
- B. Select backfill material shall be “Concrete Sand” with gradation as per Texas Department of Transportation’s requirements for Portland cement Concrete (Item 421) Fine Aggregate
  - **Fine Aggregate.** Fine aggregate shall be washed and consist of clean, hard, durable and uncoated particles of natural or manufactured sand or a combination thereof, without a mineral filler. It shall be free from frozen material or injurious amounts of salt, alkali, vegetable matter or other objectionable material and it shall not contain more than 0.5 percent by weight of clay

lumps. When the aggregate is subjected to the color test for organic impurities in accordance with Test Method Tex-408-A, the test result shall not show a color darker than standard.

When tested in accordance with Test Method Tex-401-A, the fine aggregate or combinations of aggregates, shall conform to the gradation requirements shown in following table.

FINE AGGREGATE GRADATION CHART								
	(% ) Percent Retained on Each Sieve							
Aggregate Grade No.	3/8 in.	No.4	No.8	No.16	No. 30	No. 50	No. 100	No. 200
1	0	0 - 5	0 - 20	15 - 20	35 - 75	65 - 90	90 - 100	97 - 100

- Mineral Fillers are not permitted.
- Native soils may be placed on top of the select backfill material but should be free from lumps, cobbles, and other deleterious material. This soil should not be compacted with compaction equipment.

**Approved Utility Protection Systems Manufacturers meeting All Required Section Specifications:**

1) **SuperVoid Systems, LLC**

[www.SuperVoid.com](http://www.SuperVoid.com)

1172 County Rd. 24

Prattville, Alabama 36067

Larry W. Primm  
Founder

334-730-3614

[Lprimm@SuperVoid.com](mailto:Lprimm@SuperVoid.com)

David S. Primm, P.E.  
Chief Engineer

334-221-5761

[primmd@SuperVoid.com](mailto:primmd@SuperVoid.com)

2) **Other Utility Protection Systems manufacturers must meet ALL of the requirements stated in these specifications and be approved prior to project bid in order to be considered.**

Division \_\_\_\_\_

Sections \_\_\_\_\_

## **GENERAL SPECIFICATIONS FOR CONCRETE VOID FORM SYSTEMS / UTILITY PROTECTIONS SYSTEMS PERMANENT RIGID SOIL RETAINER**

### 1. Overview:

This specification covers Permanent Rigid Soil Retainers, hereinafter referred to as “Rigid Retainers,” also known as “Rib Retainers. Rigid Retainers serve as soil retainers, which maintain and preserve void envelopes beneath structural concrete and other critical building systems and components, thereby isolating them from the potential damaging effects of expansive soils. The Rigid Retainers furnished for this project shall be in accordance with these specifications and in reasonably close conformity with the lines, grades, design and dimensions shown on the plans or as established by the Engineer. The Rigid Retainers shall be resistant to water and UV rays and shall be chiefly comprised of extruded or injection molded High Density Polyethylene (HDPE), which is structurally efficient and non-biodegradable. **The HDPE shall contain a minimum of 95% RECYCLED material.** (5% for colorant and plastic foaming additives) In situations where two or more specifications apply to this work, the most stringent requirements shall govern.

### 2. Rigid Retainer Structure:

- a) Rigid Retainers shall maintain a dimensionally stable void space beneath structural concrete and other critical building systems and components by physically restraining backfill material from entering the void space. The Rigid Retainers shall have sufficient structural strength to maintain the intended void space, without excessive deflection, while experiencing the anticipated lateral earth pressures.
- b) The Rigid Retainers shall be designed to perform as a permanent soil retaining structure which shall remain in place after construction and shall not be reused.
- c) For “**Best Practice Standards**,” the Rigid Retainers recommended installation is to overlap concrete castings by at least six (6) inches and extend a minimum of at least six (6) inches into the subgrade.
- d) Rigid Retainers should be secured to the concrete at the top with at least three (3) anchors of sufficient size and securing strength, one at each end of the overlapping joint seal design and one centered.
- e) A “**Minimum Design Standard**,” for the Rigid Retainers shall be designed to overlap concrete castings by at least three (3) inches and extend a minimum of at least three (3) inches into the subgrade.

### 3. Rigid Retainer Material:

- a) The Rigid Retainers shall be constructed from extruded or injection molded High Density Polyethylene (HDPE).
- b) The HDPE material shall be either HDPE-8 (Crate Grade) or HDPE-8 (Pail Grade) **and shall contain a minimum of 95% RECYCLED material.** (5% for colorant and plastic foaming additives)
- c) The HDPE shall conform to the following: ASTM D 1238 or ASTM D 1238E, ASTM D 4883  
ASTM D 638, ASTM D 790, ASTM D 256, ASTM D 2240 and ASTM D 648.

d) Rigid Retainers shall be manufactured entirely within the United States.

4. Rigid Retainer Material, Minimum Physical Properties Requirements:

- a) Rigid Retainer shall be naturally waterproof in terms of its intended use in this section.
- b) Rigid Retainer shall have negligible buoyancy.
- c) Rigid Retainer shall maintain structural integrity in 100% relative humidity.
- d) Rigid Retainer material shall be non-biodegradable.

5. Rigid Retainer Material, Minimum Performance Requirements:

- a) Rigid Retainers material shall provide sufficient dynamic live and dead load support capacities of but not limited to all loads common to this type of construction;
  - Installation of backfill material – construction live loads
  - Manpower and foot traffic loads
- b) Rigid Retainers material shall possess sufficient structural strength to resist anticipated lateral earth pressures.
- c) Rigid Retainers must be able to be delivered and stored unprotected in the open jobsite environment for a minimum of 90 days without loss of design strength.
- d) The structural integrity and installation of the Rigid Retainer shall be functionally unaffected by high/low ambient temperatures and elevated surface temperatures from direct sunlight extremes, above or sub-freezing, frozen soil and ice buildup.
- e) Rigid Retainer material strength shall not be affected by becoming damp, wet, or when completely submerged in standing water.
- f) These Rigid Retainer general specifications, with recommended application height and position adjustments, also apply to other Rigid Retainer assemblies such as, **SV** – Pipe Void Systems.

6. Rigid Retainer, Industry History:

- a) Rigid Retainer must have an industry history of providing consistent performance integrity during and after all types of weather event applications, while in readiness storage or installed, without the threat of partial or full section collapse during or after backfill.



**Approved Rigid Retainers Manufacturers meeting All Required Section Specifications:**

1) **SuperVoid Systems, LLC**

[www.SuperVoid.com](http://www.SuperVoid.com)

1172 County Rd. 24

Prattville, Alabama 36067

Larry W. Primm

Founder

334-730-3614

[Lprimm@SuperVoid.com](mailto:Lprimm@SuperVoid.com)

David S. Primm, P.E.

Chief Engineer

334-221-5761

[primmd@SuperVoid.com](mailto:primmd@SuperVoid.com)

- 2) **Other Retainer manufacturers must meet ALL of the requirements stated in these specifications and be approved prior to project bid in order to be considered.**

EXAMPLE

Division \_\_\_\_\_

Sections \_\_\_\_\_

## **GENERAL SPECIFICATIONS FOR PIPE CLAMP HANGER SYSTEM**

### 1. Overview:

This specification covers the Pipe Clamp Hanger System as manufactured by SuperVoid Systems, LLC. The Pipe Clamp Hanger System is an assemblage of all Stainless Steel components and is intended for use as part of the overall SuperVoid Pipe Void Systems, but may be used for other applications. The Pipe Clamp Hanger is specifically designed to aid construction, minimize pipe movement potential, and to distribute loads around the circumference of the pipe.

### 2. Pipe Clamp Hanger Structure:

- A. The Pipe Clamp Hanger shall be constructed from flat bar material which shall be shaped such that it will have appropriate curvature to match the outer diameter of the corresponding pipe and have a flange on each side of the curve. Bolt holes in the flanges allow for the upper and lower pieces to be bolted together holding the Pipe Clamp Hanger firmly in place.
- B. The upper piece of the Pipe Clamp Hanger shall mirror the lower piece, but shall have a coupling nut welded to the top of it. The coupling nut is for receiving the threaded rod which ties the Pipe Clamp Hanger to the concrete slab above it. The coupling nut shall possess a fillet weld around the entire base connecting it entirely to the Pipe Clamp Hanger's upper piece.

### 3. Pipe Clamp Hanger Material:

- A. The Pipe Clamp Hanger shall be constructed from flat bar material which is 304 Stainless Steel. The fasteners and threaded rod used shall be constructed from 18-8 Stainless Steel.

### 4. All assembly and/or fabrications of the Pipe Clamp Hanger shall occur entirely within the United States.

---

## **Approved Utility Stabilization Systems Manufacturers meeting All Required Section Specifications:**

### 1) **SuperVoid Systems, LLC**

[www.SuperVoid.com](http://www.SuperVoid.com)

1172 County Rd. 24, Prattville, Alabama 36067

Larry W. Primm

David S. Primm, P.E.

Founder

Chief Engineer

334-730-3614

334-221-5761

[Lprimm@SuperVoid.com](mailto:Lprimm@SuperVoid.com)

[primmd@SuperVoid.com](mailto:primmd@SuperVoid.com)

### 2) **Other Pipe Clamp Hanger manufacturers must meet ALL of the requirements stated in these specifications and be approved prior to project bid in order to be considered.**